

BEZILLO[®]

SUPERIOR QUALITY PRODUCTS.

BEZILLO KRYSTAL - TRANSPARENT SOLID

Knife Grade Solid Glue for Natural Stones, Quartz & Ceramic.



BEZILLO KRYSTAL - TRANSPARENT SOLID

PRODUCT DESCRIPTION

Thanks to its particular formula Krystal - Transparent Solid it remains very transparent when hardened, perfect for obtaining impeccable visible glueing.

Suitable for bonding stone, ceramic, stoneware, quartz agglomerate and marble agglomerates.

INSTRUCTIONS OF USE

In order to maximize product performances, the following instructions should be followed:

- Before using the putty, check that the surface to be bonded is dry, clean and free of dust.
- Use a spatula to take the necessary quantity from the can of Krystal and add 1-3% of liquid hardener.
- Be careful not to add the liquid hardener inside the can of Krystal.
- Mix well and use the product. Do not put the unused putty back into the jar.
- To color the Krystal - Transparent Solid use Bezillo Colorant Paste, first add the color to the mastic, max 3%, then add the hardener paste.

ADVANTAGES



... Superior quality extra clear knife grade glue



... Excellent adhesion & reactivity in all temperatures



... Easy to mix color



... Low shrinkage



... Used by professionals

SAFETY RULES

The information provided in this data sheet is based on our experience. We ensure the perfect quality of the products. However, since the use is beyond our control, we do not take responsibility for the result obtained.

It is the customer's obligation to verify that the use of the product takes place in accordance with the laws, legislation and patents of the customer's country.

SHELF LIFE

The products will last at least 12 months under normal conditions between 18-25 ° C, away from sources of heat, humidity and sunlight.

TECHNICAL DATA

Component A composition: unsaturated polyester resin and mineral fillers.

Component B composition: liquid hardener.

Ratio of Krystal (part A) / catalyst (part B): 100 parts of A + 1-3 parts of B.

Gel time at 25 ° C: 5-6 minutes

Minimum use temperature: 5 ° C

DISCLAIMER

This information is true and accurate to the best of our knowledge and belief, but since the circumstances of use and any labour required are out of our control, the end user must verify beforehand that the product is appropriate for his particular application. No responsibility can be accepted, and no warranty can be provided by our Representatives, Agents, or Distributors. The end user should make sure he has read our most recent material and that the products are sold in accordance with our Standard Conditions of Sale.



EXPERIENCE THE DIFFERENCE!!

BETON STONE SOLUTIONS INDIA PVT LTD

+91 99301 28291 / +91 83286 36546

info@betonstonesolutions.com | www.betonstonesolutions.com

HEAD OFFICE - INDIA

B/2, Amrat Niwas, 15th
Sarojini Road, Ville Parle
(W), Mumbai - 400056, India.

REGIONAL OFFICE - INDIA

Plot No.18, Saibabanagar
Colony, Tellapur, R.C. Puram,
Sangareddy, Hyderabad, India.

ITALY OFFICE

Via Monte Cengio,
11/0 36073, Cornedo
Vicentino (VI) Italy.

DUBAI OFFICE

P.O. Box
239697,
Dubai UAE.